



Audiotech Digital Signal Corporation Siren Selection Chart

<p>MODEL 2</p>  <p>Level: 102 dBC @ 100 ft. 70 dB Range: 1,000 ft. Power: 120 or 240 VAC Weight: 70 lbs. Battery Backup: No Works with VEDETTE Controller</p>	<p>3V8-H</p>  <p>Level: 109 dBC @ 100 ft. 70 dB Range: 2,000 ft. Power: AC or DC (AC single or 3-ph) Weight: 250 lbs. Battery Backup: No Works with VEDETTE Controller</p>	<p>STH10</p>  <p>Level: 115 dBC @ 100 ft. 70 dB Range: 2,400 ft. Power: 208-240 VAC, 3-phase only Weight: 400 lbs. Battery Backup: No Works with VEDETTE Controller</p>	<p>7V8</p>  <p>Level: 112 dBC @ 100 ft. 70 dB Range: 2,500 ft. Power: AC or DC (AC single or 3-ph) Weight: 350 lbs. Battery Backup: Optional Works with VEDETTE Controller</p>
<p>15V2T</p>  <p>Two-Tone Sound!</p> <p>Level: 122 dBC @ 100 ft. 70 dB Range: 4,700 ft. Power: AC or DC (AC single or 3-ph) Weight: 750 lbs. Battery Backup: Optional Works with VEDETTE Controller</p>	<p>2001 AC/DC</p>  <p>Our LOUDEST Siren!</p> <p>Level: 128 dBC @ 100 ft. 70 dB Range: 5,600 ft. Power: (2001AC) 240 VAC Weight: 410 lbs. Battery backup standard on 2001DC Works with VEDETTE Controller</p>	<p>Modulator</p>  <p>100% Electronic Siren</p> <p>Level: 106 to 121 dBC @ 100 ft. 70 dB Range: 1,200 ft. to 4,500 ft. Power: 120 VAC Weight: 181 to 760 lbs. Battery backup included Uses a proprietary controller</p>	<p>F-2</p>  <p>Use Indoors or Outdoors</p> <p>Level: 117 dBC @ 10 ft. Power: AC: 120/240; DC: 110 Weight: 11 lbs. Available in stainless steel Perfect size for industrial applications Works with VEDETTE Controller</p>



**Use the Vedette Siren Controller
for reliable siren activation everytime!**

**Toll-free: (800) 99-SIREN
(845) 888-8000
Online at: www.adsig.com**